Monroe County Surveyor's Office Corner ID: Polk_I10

Polk_I10

LAND CORNER RECORD

Index: K-9	Corner: N 1/16 BETWEEN SEC 16 & 17			*State of Indiana - Hoosier National Forest*
Section: 16, 17	Township: 7N	Range: 1E	P.M.: 2nd	County: Monroe
Coordinate:	Lat./N:		Lon./E:	Datum:

CORNER HISTORY: (Chronological history of corner)

1.) Date of Survey:	Surveyor:	Monument:	Recording Information:	
1980	T. Cummings	3" galv. pipe	USFS Records	
Reference Objects:	Species:	Diameter:	Bearing:	Distance:
	W. Oak	12"	S 14° E	12.1'
	Maple	4"	N 71° W	2.25'
Evidence Found:				
Monument Found:	Found 3" dia. steel pipe with a 3" brass disk, 1 3' above grade.			

Monument Photograph:

2.) Date of Survey:	Surveyor:	Monument:	Recording Information:	
Reference Objects:	Species:	Diameter:	Bearing:	Distance:
Evidence Found:				
Monument Found:				

ACCESSORIES: Bearing and distances from monument to witness object.

Reference Objects:	Object or Tree Species:	Diameter:	Bearing:	Distance:
	Maple	8"	N 56° E	7.42'
	Maple	6"	S 65° W	15.96'
	W. Oak	18"	S 14° E	12.20'
Monument Found or Set:	Found 3" dia. steel pipe with a 3" brass disk, 1.3' above grade.			

MONUMENT SKETCH



NARRATIVE REFERENCE:

The monument is a 3" dia. steel pipe with a 3" brass disk, 1.3' above grade. Midway up a northerly facing slope. ± 25' east of a small ravine & ± 20' south of another small ravine.

SECTION DIAGRAM



Corner Location = ●

PERPETUATION RECORD:

Monument found undisturbed per 1980 Land Corner Record. One existing bearing tree was remarked. Established two new bearing trees.

Accepted by the Monroe County Surveyor Review Board on August 6, 2019.

Section: 16, 17	Prepared By: BRG # 7308	Date: 12/27/2012

Index No. K9 (Alphabetical – Numerical)

LAND CORNER RECORD
(RECTANGULAR SURVEYS)

R9-7150-4 (Rev. 6/13/67) GPO 802-127

T. 7N R. 1E 2nd Mer. N.F. Hoosier County Monroe State In.

1/16 Corner common to sections 16, 17, and

EXISTING SURVEYS

Original Government Survey

Year surveyed

Original monument (Wood post, stone, pile of stones, pipe, etc.)

Bearing Trees

Species

Original Evidence Found

Year of search By

Monument found

Original Bearing Trees Found

Species

Diameter

Evidence of Subsequent Corner Restoration Found

search 1980 By Tim Cummings

Bearing Trees, Reference Objects

5/6/81
T.7N R.1E
Sec. 17, 16
N 1/16
0.2' N-W of corner
3" steel
3" brass cap
14" out of ground
surround. by hard
of rocks
75' E of gravel
road, 30' S intersect. of
2 small ravines
on top of N-S ridge
BT
W. Oak
4"
N 71° E
2.3'
BT
W. Oak
10"
S 14° W
12.1'

Sketch

○ Corner ▨ F.S. Land

At time of search:

1. Did you have the record description? Yes ____ No ____

2. How was search area located? Pacing, chaining, photos, maps, etc.

3. Man hours spent in search

4. Do you think additional search might recover evidence? Yes ____ No —

5. Signature T. Cummings

Relation of Evidence to Record Features Along Section Lines

Section line to sections

Object

Record distance

Measured distance

Other Evidence

Describe evidence of use and occupation such as roads, fences, clearings, timber cutting lines, plantations, etc.. Cite source of testimony if any.

Fence running East and West. Located app. 150' East of gravel rd. and on East side of hollow, on small finger between two drainages. There is a tree line running East and West, on old overgrown field app. 80' to the Northeast.

Perpetuation Record

Monument and accessories established. Include brief description of area.

3" dia. galvinized pipe w/brass cap	
B. T.	B. T.
White Oak	Maple
12" DBH	4" DBH
S 14° E	N 71° W
12.1'	2.25'

Certified corner restoration certificate prepared: Yes ____ No ____

Filed in county records at ____ Date ____ County Document No. ____

Identified on aerial photo No. ____ Which is filed at ____